

QUARRY MINING

& CONSTRUCTION EQUIPMENT PTY LTD

QUALITY

INNOVATION

EXPERTISE

GROUT PACKER PROCEDURE:

- Insert Packer in the drill hole and expand by means of handle and threaded tube until packer is secure in the hole. Test security by trying to pull out by hand.
- Packers are designed to withstand pressure generated by a Clark M150 Grout Pump and are not to exceed 500psi.
- Attach grout hoses and secure connection with safety clips before applying grout pressure.
- After completing grouting, close valve at entrance to Grout Packer
- Packer can be released and removed after grout has set and while it is still green.

Various sizes available

- Hole bore Ø35 to Ø110mm
- Lengths from 0.5m to 2m
- Special sizes made on request

Packer Length

Packer length must be appropriate to the length of the hole and when expanded must be secure in the hole.

APPLICATIONS

- ✓ Grout Injection
- ✓ De-watering of strata
- ✓ Slab jacking
- ✓ Gas drainage



WWW.QUARRYMINING.COM

EXPERTISE YOU CAN DEPEND ON

NSW: 9/14 Yangan Drive, Beresfield 2322 ph: +61 (0)2 4966 5028 fax: +61 (0)2 4910 9022 e: orders@quarrymining.com

QLD: 5/35 Iridium Drive, Paget 4740 ph: +61 (0)7 4998 5295 fax: +61 (0)7 4805 6126 e: ordersqld@quarrymining.com

VIC: 21 Trevi Cres, Tullamarine 3043 ph: +61 (0)499 808 299 e: orders@quarrymining.com