

SALES - HIRE - SERVICE

TOP MOUNT ROOFBOLTER

SUPERIOR UNIT - HIGH TORQUE, THRUST AND RELIABILITY

- Simple operation
- Energy saving motor
- Lightweight
- Cone and Cup bearing
- Fingertip control
- Advanced leg components
- Reduced noise emissions



TECHNICAL SPECIFICATIONS

	@552 kPa	@689 kPa
Motor Size	95 mm	95 mm
RPM (no load)	750	800
Air Consumption	4.5 m ³ /min	5.4 m ³ /min
Water Supply Pressure (recommended)	861-1206 kPa	861-1206 kPa
Water Flow Rate	54 L/min	54 L/min
Stall Torque	161 Nm	201 Nm
Torque through clutch	339 Nm	339 Nm
Maxi Leg thrust		
Stage 1	903 kgf	1129 kgf
Stage 2	690 kgf	863 kgf
Stage 3	487 kgf	609 kgf
Noise level	84 dB(A)	90 dB(A)
3 Stage Models	Collapsed Length (mm)	Extended Length (mm)
70-LDL-035	850	1260
70-LDL-045E	1050	2070
70-LDL-055E	1135	2390
70-LDL-065E	1350	3100
70-LDL-075E	1510	3725

Refer to OEM of roofbolter operators guide and safety points for safe working practices.

NOTE:
 Other styles and sizes are available. A full range of spare parts is available for all equipment.

